



## BPU 3050A US

### Reversible vibratory plate

Maximum compaction in the tightest spaces

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

## Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

## Technical Data

### ■ Mechanical - Output Details

Centrifugal force	30 kN
Area capacity	570.0 m <sup>2</sup> /h
Forward Running	19.0 m/min
Gradeability	36.4 %
Vibrations (Hz)	90.0 Hz

### ■ Mechanical Details

Length Baseplate	703.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	1,101.0 mm
Height Cover frame	746.0 mm

Thickness Baseplate	10.0 mm
Operating weight	166.0 kg
Ground clearance	746.0 - 856.0 mm

### ■ Engine

Effective power	5.6 KW
Nominal Engine speed	2,800.0 1/min

### ■ Environment Data

HAV summation (average value)	2.8 m/s <sup>2</sup>
HAV summation (Standard)	EN 500-4

### ■ Electrical System

Coding options	0
Remote Control Range	0.0 m

Available engines

Honda GX270-UT2X-QA-4-SD

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	270 cm3
Fuel	Gasoline
Fuel consumption	1.60 L/hr
Tank capacity	5.30 l
Effective power	5.10 KW
Nominal Engine speed	3,600 1/min
Standard (Effective power)	SAE J1349
Operating power	5.1 KW
Operating Engine speed	3,600 1/min
Standard (Operating power)	ISO 3046 IFN
Starter type	Recoil starter
Engine Manufacturer	Honda